



RA 3

Ø -0,5 0,5-0,7 0,7-0,9 0,9-1,4 1,4-2,2 2,2-3,5 3,5-5,0 5,0-7,0 7,0-9,0 9,0-15,0 15,0-25,0 25,0-40,0

TYPE	RA 3-0,5	RA 3-0,7	RA 3-0,9	RA 3-1,4	RA 3-2,2	RA 3-3,5	RA 3-5,0	RA 3-7,0	RA 3-9,0	RA 3-15,0	RA 3-25,0	RA 3-40,0
A	37	43	57	74	89	108	118	143	169	220	346	405
B	32	37	51	65	77	93	100	125	145	190	310	360
C	14	17	25	32	36	46,5	60	72	79	98	120,5	148
D	7	10	17	21	26	32	40	52	62	80	110	125
E	4	4	5	6	5	8	8	10	12,5	15	15	20
F	36	44	71	90	106	132	156	212	257	327	398	475
G	8	10	16	20	22	25	30	35	40	50	60	80
H	16	18,5	25,5	32,5	38,5	46,5	50	62,5	72,5	95	155	180
K	16	24	33	45	50	65,5	75	90	102,5	140	255	280
L	44	52	81	102	116	148	172	232	282	357	428	515
M	3,5	3,5	6,5	7	7	9	9	13	13	17,5	17,5	17,5
N	10	13	20	24,5	27	33	44	54	56	69,5	87	111
O	16	13	18	20	27	27,5	25	35	42,5	50	55	80
P	40	47	60	80	96	116,5	128	155	184	239	369	433
kg	0,1	0,2	0,4	0,8	1,1	2,1	2,4	6,2	10	21	50	90
WR	7	10	17	21	26	32	40	520	62	800	110	1250
F [N]	0,5	0,7	1,5	3	15	67	198	280	570	950	1450	2250

Richtapparat mit einzeln verstellbaren Rollen
Dresseur avec galets réglables séparément
Straightener with rollers separately adjustable

