



RTS 7 3/4

Ø -0,3 0,3-0,5 0,5-0,9 0,9-1,5 1,5-3,0 3,0-5,0 5,0-7,0 7,0-9,0

| TYPE | RTS 7-0,3 3/4 | RTS 7-0,5 3/4 | RTS 7-0,9 3/4 | RTS 7-1,5 3/4 | RTS 7-3,0 3/4 | RTS 7-5,0 3/4 | RTS 7-7,0 3/4 | RTS 7-9,0 3/4 |
|----------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| A | 63 | 89,5 | 99 | 138 | 146 | 185 | 250 | 275 |
| B/B1 | 45/12 | 62/20 | 73/20 | 102/27 | 110/27 | 140/35 | 190/45 | 210/50 |
| C | 33 | 35 | 40 | 51 | 51 | 60 | 70 | 70 |
| D | 4 | 7 | 17 | 23 | 31 | 40 | 52 | 62 |
| E | 4 | 5 | 6 | 6 | 6 | 8,5 | 12 | 12 |
| F | 54 | 68 | 100 | 143 | 167 | 193 | 376 | 436 |
| G | 12 | 15 | 15 | 20 | 20 | 20 | 25 | 25 |
| H | 17 | 24 | 28 | 44 | 48 | 58 | 83 | 94 |
| K | 25 | 45 | 53 | 82 | 90 | 114 | 150 | 170 |
| L | 62 | 78 | 112 | 155 | 179 | 210 | 400 | 460 |
| M | 4,5 | 4,5 | 5,5 | 6,6 | 6,6 | 9 | 11 | 13,5 |
| N | 13,8 | 17,5 | 19 | 24,5 | 28 | 30 | 37 | 37 |
| O | | 17 | 20 | 20 | 20 | 26 | 40 | 40 |
| P | 6 | 7,5 | 7,5 | 10 | 10 | 10 | 12,5 | 12,5 |
| S | M4 | M5 | M6 | M8 | M8 | M8 | M12 | M12 |
| T | 5 | 6 | 6 | 8 | 8 | 8,5 | 15 | 15 |
| SW1/SW2 | 3/7 | 4/10 | 5/12 | 8/13 | 8/13 | 8/19 | 10/24 | 10/24 |

kg 0,3 0,6 1,0 2,5 3,5 6,0 17,5 21,5

WR 4 7 17 23 31 40 520 62

F [N] 10 12 25 59 353 569 951 1374

Richtapparat mit einzeln verstellbaren Rollen und Schnellverschluß
Dresseur avec des galets réglables séparément et fermeture rapide
Straightener with separately adjustable rollers and quick-closing

